



Variable-displacement pumps




Before use, carefully read the GENERAL INSTRUCTIONS FOR USE OF OPEN CIRCUIT AXIAL PISTON PUMPS.




HPA4C	Nominal displacement		Swash plate °	Continuous pressure		Intermittent pressure		Peak pressure		Rotational speed		Weight	
	cm ³	in ³		bar	psi	bar	psi	bar	psi	min ⁻¹	min ⁻¹	kg	lbs
34	34	2,06	14	280	4060	320	4640	350	5075	2800	500	23	52,8
46	46	2,51	19	280	4060	320	4640	350	5075	2800	500	23	52,8
58	58	3,54	17	250	3625	300	4350	320	4640	2650	500	24	57,2
65	65	3,97	18	250	3625	300	4350	320	4640	2500	500	24	57,2

B SAE B




1 SAE 15T 16/32 DP




Max. torque 460 Nm

6 CYLINDRICAL D22.22





Max. torque 210 Nm

9 SAE 13T 16/32 DP





Max. torque 310 Nm





S **N** Side right rotation







S **N** Side left rotation




R **T** Rear right rotation



R **T** Rear left rotation




Type G




Type	M		P	
		Nm	mm	in
G1	Port ISO 1179-1 - G 1/8	17	14	0,55
G6	Port ISO 1179-1 - G 3/4	90	23	0.91

Type U



Type	Dim.	N		P		Q		M	
		mm	in	mm	in	mm	in		Nm
U2	1/4"	17	0,67	12	0,47	0,3	0,01	Port ISO 11926-1-7/16-20	17
U6	3/4"	42	1,65	20	0,79	0,3	0,01	Port ISO 11926-1-1 1/16-12	90

Type N






Type	M		N		Q		P		O	
	mm	in	mm	in	mm	in	mm	in		Nm
N7	25	0,98	52,4	2,06	26,2	1,03	20	0,79	M10	38
N9	38	1,5	69,9	2,75	35,7	1,41	20	0,79	M12	70

Combinations

Type	Inlet S	Outlet A-B	Drain port L1-L2	Pilot pressure LS (x)
G	N9	N7	G6	G2
U	N9	N7	U6	G2
R	N9	N7	G6	G1
T	N9	N7	U6	U2




C

Constant torque control



Working pressure bar - psi	Differential pressure		
	14 bar - 203 psi	21 bar - 305 psi	25 bar - 363 psi
180 - 2610	A	B	C
210 - 3045	E	F	G
250 - 3625	I	L	M
280 - 4060	O	P	Q
320 - 4640	S	T	U
350 - 5075	Z	X	Y




E Electro-proportional 12 V + hydraulic



Working pressure bar - psi	Differential pressure		
	14 bar - 203 psi	21 bar- 305 psi	25 bar- 363 psi
180 - 2610	A	B	C
210 - 3045	E	F	G
250 - 3625	I	L	M
280 - 4060	O	P	Q
320 - 4640	S	T	U
350 - 5075	Z	X	Y




F

Electro-proportional 24 V + hydraulic



Working pressure bar - psi	Differential pressure		
	14 bar - 203 psi	21 bar - 305 psi	25 bar - 363 psi
180 - 2610	A	B	C
210 - 3045	E	F	G
250 - 3625	I	L	M
280 - 4060	O	P	Q
320 - 4640	S	T	U
350 - 5075	Z	X	Y




L Hydraulic LS



Working pressure bar - psi	Differential pressure		
	14 bar - 203 psi	21 bar - 305 psi	25 bar - 363 psi
180 - 2610	A	B	C
210 - 3045	E	F	G
250 - 3625	I	L	M
280 - 4060	O	P	Q
320 - 4640	S	T	U
350 - 5075	Z	X	Y




P

Constant pressure regulator



Code	Working pressure
Differential pressure 21 bar	bar - psi
D	180 - 2610
H	210 - 3045
N	250 - 3625
R	280 - 4060
V	320 - 4640
W	350 - 5075




R Remote control pressure regulator



Code	Working pressure
Differential pressure 21 bar	bar - psi
D	180 - 2610
H	210 - 3045
N	250 - 3625
R	280 - 4060
V	320 - 4640
W	350 - 5075


S

Fan drives




Working pressure bar - psi	Differential pressure		
	14 bar - 203 psi	21 bar - 305 psi	25 bar - 363 psi
180 - 2610	A	B	C
210 - 3045	E	F	G
250 - 3625	I	L	M
280 - 4060	O	P	Q
320 - 4640	S	T	U
350 - 5075	Z	X	Y

5 SAE A



6 SAE B



	1	2	3	4	5	6	7	8	9	10	11	12	13	
HPA4C														
1 2	Displacement													
	34				46				58			65		
3	Direction of rotation													
	R	Right			L	Left								
4	Flanges													
	B	SAE B												
5	Shaft profile													
	1	SAE 15T 16/32 DP			6	CYLINDRICAL D22.22			9	SAE 13T 16/32 DP				
6	Type of ports													
	S	Gas-Uses SAE side			N	Unf-Uses SAE side			R	Gas-Uses SAE rear			T	Unf-Uses SAE rear
7	Controls													
	C	Constant torque control			F	Electro-proportional 24 V + hydraulic LS			P	Constant pressure regulator			S	Fan drives
	E	Electro-proportional 12 V + hydraulic LS			L	Pressure/flow rate regulator-hydraulic LS			R	Remote control pressure regulator				
8	Command Set													
	...	See pertinent tables												
9	Versions													
	0	No special fittings			5	SAE A			6	SAE B				
10	Accessories													
	0	No option			O	Pressure sensor			S	Multiple accessories				
	A	Angle sensor			P	Paint								
11 12 13	Special versions													
	...													